

1573F

VTACK™ FLASHING TAPE



HEAVY DUTY PERFORMANCE

Technical Data

1573F VTACK™ Flashing Tape is a multi-layer material, consisting of polyester and foil lamination, coated with an aggressive cold weather solvent acrylic adhesive, protected with a 50mm split-silicone release Kraft paper liner for ease of application. The 1573F is ideal for use as a self-adhesive flashing tape for demanding commercial and residential applications. Applies easily at high and low temperatures. Flame resistant meets UL723 and AS1530.3 flammability rating.



FEATURES & BENEFITS:

- ***Special split release liner for ease of application***
- ***AS1530.3, UL723-2008 Fire Rated Compliant***
- ***Durable Aluminum Backing***
- ***Install easy self-adhering***
- ***Closure system designed for use as a complete vapor seal***
- ***An ideal efficient barrier material prevents ingress of moisture***
- ***Long serviceable life in and outdoors***

ISO9001 CERTIFIED

AFC INDUSTRIES

TECHNICAL DATA August 2019

PROPERTIES	METRIC	ENGLISH	TEST METHOD
Backing Thickness	80 Micron	3.2 Mil	PSTC-133 / ASTM D 3652
Total Thickness	120 Micron	4.8 Mil	PSTC-133 / ASTM D 3652
Permeance (WVTR)	0 ng/N.s	0 perm	ASTM E96, Procedure
Adhesion to Steel	15 N/25mm	64.8 Oz./In.	PSTC-101 / ASTM D 3330
Tack Rolling Ball	5 cm	2.0 In.	PSTC-6 / ASTM D 3121
Tensile Strength	200 N/25mm	45.3 Lb/In	PSTC-131 / ASTM D 3759
Elongation	25 %.	25 %	PSTC-131 / ASTM D 3759
Service Temperature	-30 ~ +100 °C	-22 ~ +212 °F	-----
Applying Temperature	+10 ~ 40 °C	+50 ~ +105 °F	-----
Fire Rating	25 / 50 & Class O	25 / 50 & Class O	UL723 & BS476 Pt. 6 & 7
Volatile Organic Compound (VOC)	< 1% of the weight of the product supplied		
Ozone Depletion – ODP	ODP Free (will not cause ozone depletion)		

PRODUCT SIZE AVAILABLE:

Log Roll: 200mm x 50m (contact AFC for other custom sizes)

STORAGE & SHELF LIFE:

12 months when stored at 21°C (70°F) / 50% relative humidity out of direct sunlight.

The technical information, recommendations and other statements contained in this document are based upon tests or experience that AFC believes are reliable, but the accuracy or completeness of such information is not guaranteed. The information supplied herein is presented in good faith and believed to be accurate to the best knowledge of the supplier. It is also predicated on normal use of the product. However, since conditions of use are beyond our control, we make no warranties, expressed or implied as to the use of this information or to the suitability of product for a particular purpose. It is essential that the user test and evaluate the AFC Industries Pty Ltd (AFC) product to determine whether it is fit for a particular purpose and user's method of application. Good results will be obtained when applied to a clean, dry surface with a suitable pressure on AFC product between +10 ~ +40°C (+50 ~ +105 °F). It is essential, as with all pressure-sensitive tapes, that the surface to which the tape is applied must be clean, dry, free of grease, oil or other contaminants.

Limited Warranty: For a period of 12 months from the date of sale, AFC Industries Pty Ltd warrants this product to be free from defects in materials and workmanship. Our only obligation will be to replace any portion providing defective, or at our option, refund the purchase price thereof. The user assumes all other risk, if any, including injury, loss or damage, direct or consequential, arising out of the use, misuse, or the inability to use this product. This warranty is in lieu of the warranties of merchantability, fitness for purpose, and all other warranties, expressed or implied. No deviation is authorised. E&OE.